



INDUSTRIAL ODORGONE

DILUTION RATES

To save on shipping cost, storage space and for safe handling, INDUSTRIAL ODORGONE is shipped in a 5-gallon BULK-BLEND concentrate to be pre-mixed to make 55-gallons of READY TO USE before calculation of your dilution rates.

Once in the READY TO USE solution OdorGone will remain stable and never need to be stirred.

(READY TO USE) Pre-Mix Instructions

Add 5-Gal. INDUSTRIAL ODORGONE BULK-BLEND to 50-Gal. of water to make 55-Gal. INDUSTRIAL ODORGONE READY TO USE Industrial Odor Neutralizer.

DILUTION RATES

From (RTU) Pre-Mix

Dilution rates and daily usage will vary based on odor intensity and the efficiency and run time of the odor control system. Location, (indoors or outdoors) weather conditions, nozzle placement, nozzle output, fog or mist particle size are all factors in determining dilutions. The optimum dilution rate is achieved when neither the odor nor the INDUSTRIAL ODORGONE can be detected.

Atomizing Nozzles (High pressure / 1000 psi / 10-microns or less)	400:1 to 3000:1
Foggers, Misters, Fans	10:1 to 800:1
Scrubbers	300:1 to 3000:1
Topical	4:1 to 600:1

INDUSTRIAL ODORGONE *“Performs Where Others Fail”*

OG INDUSTRIES, LLC
E-mail: pete@obanog.com



Phone: 1-484-461-3030

Web: www.industrialodorgone.com
Toll Free USA: 1-877-362-9831